



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 1 / 10

Safety data sheet according to U.S.A. Federal Hazcom 2012

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: SO8400NE
Product name: OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO
Chemical name and synonym: Pigment dispersion in vegetable oil based resin

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use: Concentrated colouring paste

1.3. Details of the supplier of the safety data sheet.

Name: CARVER S.r.l. Unipersonale
Full address: Via Papa Giovanni XXIII, 36
District and Country: 20090 Rodano (MI)
Italy
Tel. +39 (0)2 9500171
Fax. +39 (0)2 95320921

e-mail address of the competent person responsible for the Safety Data Sheet: sds@carver.it

Product distribution by: www.carver.it

1.4. Emergency telephone number.

For urgent inquiries refer to: 24 HOUR EMERGENCY TELEPHONE NUMBERS:
CHEMTREC - US & CANADA toll free: +1-800-424-9300
CHEMTREC - MEXICO toll free: 01-800-681-9531
CHEMTREC - GLOBAL collect calls accepted: +1-703-527-3887

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Flammable liquid, category 3
Eye irritation, category 2

Flammable liquid and vapour.
Causes serious eye irritation.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 2 / 10

SECTION 2. Hazards identification. ... / >>

P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash with water thoroughly after handling.
P280	Wear protective gloves / eye protection / face protection.
Response:	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice / attention.
P370+P378	In case of fire: use an adequate extinguishing measure to extinguish.
Storage:	
P403+P235	Store in a well-ventilated place. Keep cool.
Disposal:	
P501	Dispose of contents and/or containers to authorized waste treatment plants.

2.2. Other hazards.

READ INSTRUCTIONS BEFORE USE. DANGER OF COMBUSTION. Rags and other porous materials soaked with this product could generate self-combustion phenomena, even delayed in time, due to self-oxidation: all contaminated materials must be immersed in water and kept in an airtight metal container.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. x = Conc. % Classification:

Vegetable oil based resin

CAS. 30 ≤ x < 50

EC.

INDEX.

Pigment

CAS. 9 ≤ x < 30

EC.

INDEX.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

CAS. 64742-94-5 10 ≤ x < 30 Flammable liquid, category 4 H227, Aspiration hazard, category 1 H304

EC. 265-198-5

INDEX. 649-424-00-3

Hydrocarbons C11-14 <2% aromatic

CAS. 10 ≤ x < 30 Flammable liquid, category 4 H227, Aspiration hazard, category 1 H304

EC. 927-285-2

INDEX.

N° Reg. 01-2119480162-45

Alkylamine derivatives

CAS. 40027-38-1 1 ≤ x < 3 Serious eye damage, category 1 H318, Skin irritation, category 2 H315

EC. 254-754-2

INDEX.

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Other information:

Vegetable oil-based resin: possible spontaneous ignition of papers or textiles soaked by the substance (heat release due to self-oxidation).



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 3 / 10

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 4 / 10

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	paste
Colour	black
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	54 °C. (0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	not applicable
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 5 / 10

SECTION 9. Physical and chemical properties. ... / >>

Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0.990
Solubility	soluble in white spirits
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	>20,5 mm ² /sec (40°C)
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

May form flammable mixtures with: air.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:	Not classified (no significant component).
LC50 (Inhalation - mists / powders) of the mixture:	Not classified (no significant component).
LD50 (Oral) of the mixture:	Not classified (no significant component).
LD50 (Dermal) of the mixture:	Not classified (no significant component).

Hydrocarbons C11-14 <2% aromatic	
LD50 (Dermal).	> 5000 mg/kg Rabbit
LC50 (Inhalation).	> 5000 mg/kg Rat

SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION.



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 6 / 10

SECTION 11. Toxicological information. ... / >>

Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity.

Hydrocarbons C11-14 <2% aromatic

LC50 - for Fish.

> 1000 mg/l/96h Fish

EC50 - for Crustacea.

> 1000 mg/l/48h Tetrahymena pyriformis

12.2. Persistence and degradability.

Petroleum distillates, charcoal, vegetable extracts: they are mixtures of paraffinic, naphthenic, diterpenic and aromatic hydrocarbons.

Their behaviour on the environment depends on the concentration. In each case use, according to good working practices, avoiding disposal in the environment. As a rule, the product is poorly biodegradable.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Oil distillates, coal, plant extracts: they are blends of parafin hydrocarbons, naphthenes, diterpenes and aromatics. Their behaviour in the environment depends on their composition. In any case they should be used according to good working practice, avoiding discharging it into the environment.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Rapidly biodegradable.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

Sur la base des données disponibles, le produit ne contient pas de substances PBT ou vPvB en pourcentage supérieur à 0,1%.

12.6. Other adverse effects.

Information not available.



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 7 / 10

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: 1263

The product, if packaged in packages of less than 450 litres, is not subject to ADR regulations as stated in 2.2.3.1.5.

The product, if packaged in packages of less than 30 litres, is not subject to obligations relating to marking, labelling and package testing in accordance with 2.3.2.5 of the IMDG CODE.

14.2. UN proper shipping name.

ADR / RID:
IMDG: PAINT or PAINT RELATED MATERIAL
IATA:

14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group.

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: 30 Special Provision: -	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	Packaging instructions: 366
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 355

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.



SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

U.S. Federal Regulations.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

No component(s) listed.

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

No component(s) listed.

EPCRA 313 TRI:

No component(s) listed.

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State Regulations.

Massachusetts:

No component(s) listed.

Minnesota:

No component(s) listed.

New Jersey:

No component(s) listed.

New York:

No component(s) listed.

Pennsylvania:



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 9 / 10

SECTION 15. Regulatory information. ... / >>

Hydrocarbons C11-14 <2% aromatic (Naphta V.M. +P, High flash)

California:

No component(s) listed.

Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Candadian WHMIS.

CLASS B2: Division 2: Flammable Liquids.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Flam. Liq. 4	Flammable liquid, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H400	Very toxic to aquatic life.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112@)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit



CARVER S.r.l. Unipersonale

OILPAST NERO / BLACK / NOIR / SCHWARZ / NEGRO

Revision nr.1
Dated 10/3/2016
Printed on 10/3/2016
Page n. 10 / 10

SECTION 16. Other information. ... / >>

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

15.