



## Safety data sheet according to U.S.A. Federal Hazcom 2012

### SECTION 1. Identification of the substance/mixture and of the company/undertaking.

#### 1.1. Product identifier.

Code: SO8400TO  
Product name: OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTTE UMBRA / TIERRA SOMBRA TOSTADA  
Chemical name and synonym: Pigment dispersion in white spirit

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use: Concentrated colouring paste

#### 1.3. Details of the supplier of the safety data sheet.

Name: CARVER S.r.l. Unipersonale  
Full address: Via Papa Giovanni XXIII, 36  
District and Country: 20090 Rodano (MI)  
Italy  
Tel. +39 (0)2 9500171  
Fax. +39 (0)2 95320921

e-mail address of the competent person responsible for the Safety Data Sheet: sds@carver.it

Product distribution by: www.carver.it

#### 1.4. Emergency telephone number.

For urgent inquiries refer to: 24 HOUR EMERGENCY TELEPHONE NUMBERS:  
CHEMTREC - US & CANADA toll free: +1-800-424-9300  
CHEMTREC - MEXICO toll free: 01-800-681-9531  
CHEMTREC - GLOBAL collect calls accepted: +1-703-527-3887

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement.

Flammable liquid, category 4

Combustible liquid.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H227

Combustible liquid.

H336

May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves / eye protection / face protection.

Response:

P370+P378

In case of fire: use an adequate extinguishing measure to extinguish.



# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 2 / 9

## SECTION 2. Hazards identification. ... / >>

Storage:

**P403+P233**

Store in a well-ventilated place. Keep container tightly closed.

Disposal:

**P501**

Dispose of contents and/or containers to authorized waste treatment plants.

### 2.2. Other hazards.

READ INSTRUCTIONS BEFORE USE. DANGER OF COMBUSTION. Rags and other porous materials soaked with this product could generate self-combustion phenomena, even delayed in time, due to self-oxidation: all contaminated materials must be immersed in water and kept in an airtight metal container.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.                      x = Conc. %                      Classification:

**Pigment**

CAS.                                      50 ≤ x < 100

EC.

INDEX.

**Hydrocarbons C10, aromatics <1% naphthalene**

CAS.                                      20 ≤ x < 25                      Flammable liquid, category 4 H227, Aspiration hazard, category 1 H304,  
Specific target organ toxicity - single exposure, category 3 H336

EC.

INDEX.

N° Reg. 01-2119463583-34

**SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM**

CAS. 64742-94-5    1 ≤ x < 2                      Flammable liquid, category 4 H227, Aspiration hazard, category 1 H304

EC. 265-198-5

INDEX. 649-424-00-3

**Amines, n-sego alkyltrimethylendi-, oiled**

CAS. 61791-53-5    0 ≤ x < 0.5                      Skin corrosion, category 1B H314

EC. 263-186-4

INDEX.

\* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Other information:

Vegetable oil-based resin: possible spontaneous ignition of papers or textiles soaked by the substance (heat release due to self-oxidation).

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.



# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 3 / 9

## SECTION 4. First aid measures. ... / >>

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.



# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 4 / 9

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Information not available.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

#### HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84 and OSHA 29 CFR 1910.134.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	paste
Colour	brown
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	62 °C. (0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	not applicable
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0.99
Solubility	soluble in white spirits
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	>20,5 mm <sup>2</sup> /sec (40°C)
Explosive properties	Not available.
Oxidising properties	Not available.



AZIENDA CON SISTEMA DI GESTIONE  
AMBIENTALE CERTIFICATO DA DNV  
UNI EN ISO 14001:2004 =  
AZIENDA CON SISTEMA DI  
GESTIONE PER LA QUALITÀ  
CERTIFICATO DA DNV  
=UNI EN ISO 9001:2008=

# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 5 / 9

## SECTION 9. Physical and chemical properties. ... / >>

### 9.2. Other information.

Information not available.

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM  
May form flammable mixtures with: air.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

### 10.5. Incompatible materials.

Information not available.

### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

#### ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:	Not classified (no significant component).
LC50 (Inhalation - mists / powders) of the mixture:	Not classified (no significant component).
LD50 (Oral) of the mixture:	Not classified (no significant component).
LD50 (Dermal) of the mixture:	Not classified (no significant component).

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, and OSHA.

#### SKIN CORROSION / IRRITATION.

Does not meet the classification criteria for this hazard class.

#### SERIOUS EYE DAMAGE / IRRITATION.

Does not meet the classification criteria for this hazard class.

#### RESPIRATORY OR SKIN SENSITISATION.

Does not meet the classification criteria for this hazard class.

#### GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

#### CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

#### REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

#### STOT - SINGLE EXPOSURE.

May cause drowsiness or dizziness.



## SECTION 11. Toxicological information. ... / >>

### STOT - REPEATED EXPOSURE.

Does not meet the classification criteria for this hazard class.

### ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

## SECTION 12. Ecological information.

### 12.1. Toxicity.

Amines, n-sego alkyltrimethylendi-, oiled  
EC50 - for Crustacea.

0.01 mg//48h Dafnie

### 12.2. Persistence and degradability.

Petroleum distillates, charcoal, vegetable extracts: they are mixtures of paraffinic, naphthenic, diterpenic and aromatic hydrocarbons. Their behaviour on the environment depends on the concentration. In each case use, according to good working practices, avoiding disposal in the environment. As a rule, the product is poorly biodegradable.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM  
Rapidly biodegradable.

### 12.3. Bioaccumulative potential.

Information not available.

### 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

Information not available.

### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
CONTAMINATED PACKAGING  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

### 14.1. UN number.

Not applicable.

### 14.2. UN proper shipping name.

Not applicable.

### 14.3. Transport hazard class(es).

Not applicable.

### 14.4. Packing group.

Not applicable.



# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 7 / 9

## SECTION 14. Transport information. ... / >>

### 14.5. Environmental hazards.

Not applicable.

### 14.6. Special precautions for user.

Not applicable.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

#### U.S. Federal Regulations.

##### Clean Air Act Section 112(b):

No component(s) listed.

##### Clean Air Act Section 602 Class I Substances:

No component(s) listed.

##### Clean Air Act Section 602 Class II Substances:

No component(s) listed.

##### Clean Water Act – Priority Pollutants:

No component(s) listed.

##### Clean Water Act – Toxic Pollutants:

No component(s) listed.

##### DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

##### DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

##### EPA List of Lists:

##### 313 Category Code:

No component(s) listed.

##### EPCRA 302 EHS TPQ:

No component(s) listed.

##### EPCRA 304 EHS RQ:

No component(s) listed.

##### CERCLA RQ:

No component(s) listed.

##### EPCRA 313 TRI:

No component(s) listed.

##### RCRA Code:

No component(s) listed.

##### CAA 112 (r) RMP TQ:

No component(s) listed.

#### State Regulations.

##### Massachusetts:

No component(s) listed.



# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 8 / 9

## SECTION 15. Regulatory information. ... / >>

### Minnesota:

No component(s) listed.

### New Jersey:

No component(s) listed.

### New York:

No component(s) listed.

### Pennsylvania:

Hydrocarbons C10, aromatics <1% naphthalene (Naphta V.M. +P, High flash)

Hydrocarbons C11-14 <2% aromatic (Naphta V.M. +P, High flash)

### California:

No component(s) listed.

### Proposition 65:

This product does not contain any substances know to the State of California to cause cancer, reproductive harm or birth defects.

### International Regulations.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Canadian WHMIS.

CLASS B3: Division 3: Combustible Liquids.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 4</b>	Flammable liquid, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>H227</b>	Combustible liquid.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H400</b>	Very toxic to aquatic life.
<b>H411</b>	Toxic to aquatic life with long lasting effects.

### LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%





# CARVER S.r.l. Unipersonale

OILPAST TERRA OMBRA / BURNT UMBER / OMBRE BRULEE / GEBRANNTE UMBRA / TIERRA SOMBRA TOSTADA

Revision nr.1  
Dated 12/1/2016  
Printed on 12/1/2016  
Page n. 9 / 9

## SECTION 16. Other information. ... / >>

- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

### GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
  
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.